




## MULTIMASTER

Machines for the efficient production  
of concrete elements

Technical Data		
Usable mould dimensions:	<ul style="list-style-type: none"> <li>• Production on vibrating table:</li> <li>• Production on floor:</li> </ul>	1240 x 1000 mm 1240 x 1240 mm
Product height:	<ul style="list-style-type: none"> <li>• Production on vibrating table:</li> <li>• Production on floor:</li> </ul>	50 – 650 mm 250 – 1000 mm
Max. package height multilayer (depending on block height):		650 mm + 1 block layer height
Hopper capacity:		1600 l / 1000 l (face mix)
Machine dimensions: With face mix:		L 5040 x W 2730 x H 4080 mm L 6410 x W 2730 x H 4080 mm
Vibrator force:	<ul style="list-style-type: none"> <li>• Vibrating table:</li> <li>• Ram vibrator:</li> <li>• Mould vibrators (max. 4 pc):</li> </ul>	max. 110 kN max. 80 kN each max. 20 kN
Power rating:		45 kW
Hydraulic pressure:		210 bar

Production capacity			
Product	Dimensions	Per cycle	Per h
	Paver 200 x 100 x 60 mm	1,08 m <sup>2</sup>	100 m <sup>2</sup>
	Behaton 200 x 165 x 60 mm	0,95 m <sup>2</sup>	88 m <sup>2</sup>
	L 400 x W 200 x H 200	12 pcs.	1230 pcs.
	L 400 x W 100 x H 200	22 pcs.	2260 pcs.
	L 1000 x W 250 x H 250	3 pcs.	240 pcs.
	L 1000 x W 150 x H 250	6 pcs.	480 pcs.



### Knauer Engineering GmbH Industrieanlagen & Co. KG

Elbestraße 11 – 13 · D-82538 Geretsried · Germany  
 Tel.: +49 (0) 8171 62950 · Fax: +49 (0) 8171 64545  
 E-Mail: info@knauer.de · Web: www.knauer.de